

Product Data Sheet

SC180

Smoke Curtain

KEY SPECIFICATIONS

Headbox 0.05" galvanized mild steel with 0.08"

end caps

Rollers 2.99" coated mild steel tube

Motors 24V DC

Fabric C41000WK

Bottom Bar 0.79" x 0.79" - 0.79" x 1.57" galvanised steel

Side Guides 3.94" x 1.97" rolled steel

Electronics See separate spec sheet



STANDARDS

Tested and approved by Underwriters Laboratories LLC to Standards.

- UL1784: Air Leakage Tests of Door Assemblies and Other Opening Protectives.
- UL864: Control Units and Accessories for Fire Alarm Systems.
- UL723: Test for Surface Burning Characteristics of Building Materials.

DESIGNATIONS & SIZE LIMITATIONS

Model	SIngle Roller	Multi Roller	Max Width (ft)	Max Drop (ft)	Classification	Test Standard	Certificate / Reports
SC180	Yes	Yes	147	39	Smoke Rating	UL 1784	20120808-R26410



HEADBOX SIZES

The size of the curtain roller housing (headbox), depends on the curtain drop and width. The table below gives details of the full range of headbox sizes for the SC180 smoke protective curtains.

Type A: The standard headbox for use with curtain widths up to 16'.

Type B: Headbox for use with curtains up to 147' and limited installation height for headbox.

Type C: The standard headbox for use with curtain widths up to 147'.



WARRANTY

A manufacturer's warranty is provided for a period of one year. Exclusions may apply if any element is sublet to an unauthorized party.









